



CROWN GENERAL N.V.

Havenlaan 2 - 3980 Tessenderlo - Belgium
 Tel: +32 13 66 17 51 - Fax: +32 13 66 88 18
 Email: info@crowngeneral.be

Product Specifications

PVC-FOAM D.320/350 ST (= Standard)

<u>PARAMETERS</u>	<u>UNIT</u>	<u>VALUE</u>	<u>NORM</u>
Density	kg/m ³	320-350	
Tensile Strength	Kpa	≥ 1000	DIN 53571
Elongation at Break	%	≥ 160	DIN 53571
Tear Strength	N/mm	≥ 4	DIN 53515
Compression Set (50%/23°C/72h)	%	≤ 25	DIN 53572
Compression Deflection	Kpa	0 s. 80-310 60 s. 40-160	ASTM 1667
Shore 00 Hardness		65-80	
Waterabsorption	%	≤ 2	
Compression Waterseal		≥ 5 %	U-TEST
Flammability	mm/min	≤ 100	FMVSS 302
Temperature Range	°C	-30 / +60	
Tolerance: At G > 500 g/m ² : +/-10 % At G ≤ 500 g/m ² : +/-20 % G = weight	-	-	-

Products with different technical characteristics can be developed and manufactured at request. The above data are only for information and do not involve any guarantee. As our products are used for many purposes, we recommend our customers to do their own tests to determine the suitability of our products for their purposes and applications.